

TESTING CORD ASSEMBLIES  
ONE-CONDUCTOR CORDS  
MISCELLANEOUS  
DESCRIPTION

1. GENERAL


437

1.01 This section lists and illustrates the coded single-conductor miscellaneous cords.

1.02 This section is reissued to add the following cords:

- 26
- 437
- 540

The Equipment Test List is not affected.



Res 0.21  $\Omega$ /ft

This cord consists of tinsel conductors with green vinyl outer covering which is terminated with a 30 cord tip on one end and a 134 cord tip on the other end.


2. DESCRIPTION OF CORDS

540

26


May be ordered in length required.

Available in 3-foot, 6-foot or 9-foot lengths. (Unless otherwise specified, the 6-foot cord shall be furnished.)



Res 0.010  $\Omega$ /ft

This cord consists of stranded copper conductor with black vinyl outer covering. Replaces the 338 cord.



Res 0.21  $\Omega$ /ft

A single-conductor cord with tinsel conductors.

The color is green with vinyl outer covering.

760-MFR DISC.

(Replaced by the W1U cord.)

D-160245—MFR DISC.

KS-20533, L1 and L2—MFR DISC.

(Replaced by the W1BG and W2BF cords, respectively.)

NOTICE

Not for use or disclosure outside the  
Bell System except under written agreement