43A1 VOICE-FREQUENCY CARRIER TELEGRAPH (VFCT) SYSTEM (J70112-)

DESCRIPTION AND OPERATION

1. GENERAL

- 1.001 This addendum supplements Section 312-700-100, Issue 5. Place this pink sheet ahead of Page 1 of the section.
- 1.002 This addendum is reissued for the following reasons:
 - (a) To change entries in the Receive column of Table A.
 - (b) To add, change and delete entries in the Description column of Table F.
- 1.003 Issue 1 of this addendum was issued to add a note to Table C and correct paragraph 4.02(c).

2. CHANGES TO SECTION

ISSUE 1 CHANGES

2.001 Add the following note to Table C:

Note: When the 262C switch and 4143B network are used in a 62.5 mA neutral channel

terminal, the channel terminal must be equipped with option WY of SD-70552-01.

- 2.002 In paragraph 4.02(c) revise the following:
 - (c) In the last sentence of the fourth bullet paragraph, change clockwise to read "counterclockwise."

ISSUE 2 CHANGES

- 2.003 On Page 11, Table A, in the Receive column, fifth entry from top, change 454D to 454AH.In the same column, tenth, eleventh, and twelfth entries from top, change 454H, J, and K to 454AF, AJ, and AG, respectively.
- 2.004 On Page 25, Table F, in the Description column, twenty-first entry from top, add Hub SW, and change twenty-second entry to read Neutral DW. For the twenty-third and twenty-fourth entries, add Hub DW and Cover*, respectively. Delete Neutral DW, Hub DW, and Cover* below the twenty-fourth entry in Description column.

NOTICE

Not for use or disclosure outside the Bell System except under written agreement